

1000 Corey Road P.O. Box 886 Hutchinson, KS 67504-0886 620-665-5661 FAX: 620-665-0559 TOLL FREE: 877-464-0623 www.sdklabs.com

Page 1 of 1

Sample #

1320.25

Sample:

Water

Other ID:

CC: (Em) gatorman50@gmail.com Sampled by Connie

Larry Muryon Kitchen

REALTY EXECUTIVES

111 E 30TH

HUTCHINSON, KS 67502

Date Received:

03/24/2025

Date/Time Sampled:

3/20/2025 15:00:00

Date Reported:

03/25/2025

Total Fee:

\$74.00

ANALYSIS

	Result	Units	Date/Time Analyzed	Analyst
++Nitrate-Nitrogen - SM 4500-N03 D	3.46	mg/L	3/21/2025 14:35	SE
++Total Coliforms/100mL: SM9223BColilert	None detected	cfu/100mL	3/21/2025 16:12	MH/DH
++E. Coli/100 mL: SM9223 B-Collert	None detected	cfu/100mL	3/21/2025 16:12	MH/DH
Coliform Bacterial Condition	Acceptable		3/21/2025 16:12	MH/DH
400				

<sup>\*\*</sup>Sample receipt temperature = 22.9 degrees C.

## SDK LABORATORIES GENERAL WATER REPORT GUIDELINES

- pH: Normal range 6.5 8.5 with Reverse Osmosis/Distilled Water having a range of 5.0 6.0.
- Chloride: Levels above 250 mg/L may cause a "salty taste". Levels above 1000 mg/L are not recommended for
- Fluoride: Levels above 2.0 mg/L are not recommended.
- Total Hardness:

"Soft Water": 0 – 85 mg/L (0 – 5 grains/gallon)

"Moderately Hard Water": 85 – 150 mg/L (5 – 9 grains/gallon)

"Hard Water": 150 - 300 mg/L (9 - 18 grains/gallon)

"Very Hard Water": 300 - 500 mg/L (18 - 30 grains/gallon)

Levels above 2000 mg/L are not recommended for livestock.

Nitrate-Nitrogen:

Levels between 0 - 10 mg/L are acceptable.

Livestock Levels:

Levels between 20 – 40 mg/L may pose a risk to some livestock.

Levels above 40 mg/L are not recommended for livestock.

- Calcium and Magnesium: Cause the "Hardness" of the water.
- Sodium: Levels above 100 mg/L are considered to be high. Water softeners recharged with sodium chloride (salt) increase the sodium level.
- Sulfate: Levels above 250 mg/L may cause a mild taste and levels above 500 mg/L may cause diarrhea in both humans and livestock.
- Iron: Levels above 0.3 mg/L may cause taste, odor and staining on fixtures and laundry.
- Manganese: Levels above 0.05 mg/L may cause taste and black/grey staining on fixtures and laundry.
- Electrical Conductivity: A measurement of the conductivity of the water. Typically, the higher the electrical conductivity of the water, the higher the dissolved salts/solids.
- TDS-Total Dissolved Solids: Levels above 1000 mg/L may cause taste. Shortened water heater life may be caused by levels above 400 mg/L. Levels above 7000 mg/L are not recommended for livestock.

Source: Michael H. Bradshaw, and G. Morgan Powell, Understanding your Water Test Report, Kansas State University, October 2004 Standard Methods for the Examination of Water and Wastewater, 18th edition, 1992

<sup>\*</sup> Analysis was subcontracted to another laboratory for state compliance - see attached.

<sup>++</sup>Denotes NELAP/KDHE Accredited Method. Lab Certificate #E-10152. Results meet all requirementsof NELAC unless noted.

Methods of analysis per EPA-600 or EPA SW-846, 3rd Ed., 1986 or Standard Methods for the Examination of Water and Wastewater, 18th Edition, 1992.